



TORO-IRRIGATION DIVISION 5825 JASMINE STREET RIVERSIDE, CA 92504 TOLL FREE: 1-877-345-8676

FAX: (951) 359-1870

crc@toro.com www.toro.com

LEGEND:

- 1 570Z SPRAY HEAD 2",3",4",6",12" OR SHRUB (XF RECOMMENDED)
- ②PRECISION™ SERIES NOZZLE SCREWED INTO 570Z SPRAY HEAD AND ORIENTED TO INTENDED SPRAY AREA.
- (3) MAX. TRAJECTORY OF NOZZLE IS 20 ° SO INSTALL HEAD TO ALLOW FOR CLEARANCE OVER TALL PLANT MATERIAL.

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 065-403.



PRECISION™ SERIES ROTATING NOZZLE

065-403 REVISION DATE 08/14/2014